



Aral Getriebeöl ATF M 14

Automatic Transmission Fluid

Description

Aral Getriebeöl ATF M 14 is a high quality automatic transmission fluid approved for use in passenger car transmissions according current MB 236.14 approval.

Advantages

- Enhanced friction durability for smooth transmission performance.
- Exceptional high temperature protection to effectively resist fluid oxidation and the formation of harmful deposits.
- Superb low temperature fluidity for cold weather shifting.
- Fuel efficiency potential
- optimised for smooth shifting

Typical Characteristics

Name	Method	Units	Aral Getriebeöl ATF M 14
Density @ 15C	DIN 51757	g/ml	0.848
Colour	ASTM D6045	-	red
Flash Point, COC	DIN-ISO 2592	°C	>180
Base oil kinematic viscosity at 40°C	DIN 51562	mm ² /s	30
Viscosity, Kinematic 100C	DIN 51562-1	mm ² /s	6,3
Viscosity Index	DIN ISO 2909	None	> 170
Viscosity, Brookfield @ -40C (75W)	DIN 51398	mPa.s (cP)	11000

Product Performance Claims

MB-Approval 236.14

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeöl ATF M 14
06 Jun 2012

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg
01801-11 55 11
www.aral-lubricants.de