

# ARAL SuperTronic Longlife III 0W-30

Aral Low SAPS-Technology for maximum wear protection.



## Description

Aral SuperTronic LongLife III 0W-30 has been specifically developed for latest European cars especially from VW group vehicles to ensure maximum wear protection, cleanliness of the engine and thereby supporting the function of diesel particulate filters.

## Application

ARAL SuperTronic Longlife III 0W-30 is approved for use in vehicles requiring BMW Longlife-04, MB-Approval 229.31/ 229.51/ 229.52, Porsche C30 and VW 504 00/ 507 00 specification 0W-30 lubricant.

Please refer to your owners handbook.

## Typical Characteristics

Name	Method	Units	ARAL SuperTronic Longlife III 0W-30
Density @ 15C, Relative	DIN 51757	g/ml	0.843
Viscosity, Kinematic 100C	DIN 51562	mm <sup>2</sup> /s	12.3
Viscosity, CCS -35C	DIN 51377	mPa.s (cP)	5930
Viscosity, Kinematic 40C	DIN 51562	mm <sup>2</sup> /s	61
Viscosity Index	DIN ISO 2909	None	205
Pour Point	ASTM D5950	°C	-48
Flash Point, PMCC	ASTM D93	°C	196
Ash, Sulphated	DIN 51575	% wt	0.85

## Product Performance Claims

BMW Longlife-04

MB-Approval 229.31/ 229.51/ 229.52

Porsche C30

VW 504 00/ 507 00

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

ARAL SuperTronic Longlife III 0W-30

21 Apr 2023

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

[www.aral-lubricants.de](http://www.aral-lubricants.de)