Aral SuperTronic LL IV FE 0W-20

Fully Synthetic engine oil for gasoline or diesel engines



Description

Fully Synthetic high-performance engine oil for passenger cars:

- For gasoline or diesel engines
- Provides an outstanding anti wear performance
- High performance motor oil designed for longest drain intervals at flexible maintenance periods
- Provides less fuel and oil consumption

Application

Aral SuperTronic LL IV FE 0W-20 is suitable for use in automotive gasoline and diesel engines in vehicles from the VW group where the manufacturer recommends a VW 508 00 / 509 00 specification 0W-20 lubricant.

Typical Characteristics

Name	Method	Units	Aral SuperTronic LL IV FE 0W-20
Density @ 15C, Relative	DIN 51757	g/ml	0.84
Viscosity, Kinematic 100C	DIN 51562	mm²/s	8.0
Viscosity, CCS -35C (0W)	DIN 51377	mPa.s (cP)	4100
Viscosity, Kinematic 40C	DIN 51562	mm²/s	43
Viscosity Index	DIN ISO 2909	None	165
Pour Point	ASTM D97	°C	-48
Flash Point, PMCC	ASTM D93	°C	196
Ash, Sulphated	ASTM D874	% wt	0.76
Flash Point, COC	DIN-ISO 2592	°C	228

Product Performance Claims

VW 508 00 / 509 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral SuperTronic LL IV FE 0W-20 16 Jul 2018

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg 01801-11 55 11 www.aral-lubricants.de