

Aral Traktoral 10W-40

Super Tractor Oil Universal STOU



Description

One oil that delivers high performance & protection for engine, transmission, wet brake, hydraulic and front axles.

Advantages

- One oil simplifies servicing, avoiding misapplication
- One oil reduces inventory, saving money
- Excellent cold start protection reduces engine wear

Typical Characteristics

Name	Method	Units	Traktoral 10W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.88
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	93
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.8
Viscosity Index	ASTM D2270	None	150
Pour Point	ASTM D97	°C	-36
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	6290
Viscosity, Brookfield -18C	ASTM D2983	mPa.s (cP)	6700
Flash Point, COC	ASTM D92	°C	234

Product Performance Claims

ACEA E2

API CF-4/SF/GL-4

Approved - ZF TE-ML 06D, MF M1145

Meets - MF M1144, MF M1139, JDM J27, Ford ESN-M2C-159B

Can be used where JD J20C, Case MS1207, Ford M2C-134D, M2C-86B is specified.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Traktoral 10W-40

03 Jun 2016

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de