



Aral EcoTronic F 5W-20

High performance engine oil

Description

Aral EcoTronic F 5W-20 is a high-performance engine oil in Aral Synthetic-Technology specially engineered for Ford EcoBoost^R engines that need an oil according to Ford WSS-M2C948-B. It is also suitable for use in most modern Ford petrol engines that require an oil according to Ford WSS-M2C913-B, WSS-M2C913-C or WSS-M2C925-B (with the exception of Ford Ka, Focus ST and Focus RS). The product is able to provide extra fuel economy.

Advantages

- excellent protection against wear
- delivers superior performance under extreme cold start up conditions relative to thicker grades
- fuel economy potential

Typical Characteristics

Name	Method	Units	Aral EcoTronic F 5W-20
Density @ 15C, Relative	ASTM D1298	g/ml	0.847
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	43.51
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.2
Viscosity Index	ASTM D2270	None	166
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3450
Viscosity, HTHS 150C	ASTM D4683	cP	2.6
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	210

Product Performance Claims

Meets Ford WSS-M2C948-B

Aral EcoTronic F 5W-20

19 Aug 2013

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de